

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

1 Identification

- **Product identifier**
- **Trade name:** MC-ZINC 2.8
- **Article number:** W01.X W01.XXXX
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wasser Corporation
4118 B PL NW, Suite B
Auburn, WA 98001, US
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
EMERGENCY PHONE NUMBERS:
USA and Canada: 1-800 424-9300
International: 1-703 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

4,4'-methylenediphenyl diisocyanate

Talc (Mg₃H₂(SiO₃)₄)

diphenylmethanediisocyanate, isomeres and homologues

- **Hazard statements**

H226 Flammable liquid and vapor.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 1)

*H315 Causes skin irritation.**H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.**H317 May cause an allergic skin reaction.**H340 May cause genetic defects.**H350 May cause cancer.**H373 May cause damage to organs through prolonged or repeated exposure.***· Precautionary statements***Keep out of reach from children.**P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.**P241 Use explosion-proof electrical/ventilating/lighting/equipment.**P260 Do not breathe dust/fume/gas/mist/vapors/spray.**P284 [In case of inadequate ventilation] wear respiratory protection.**P280 Wear protective gloves / eye protection / face protection.**P240 Ground/bond container and receiving equipment.**P233 Keep container tightly closed.**P242 Use only non-sparking tools.**P243 Take precautionary measures against static discharge.**P264 Wash thoroughly after handling.**P272 Contaminated work clothing must not be allowed out of the workplace.**P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**P321 Specific treatment (see on this label).**P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.**P363 Wash contaminated clothing before reuse.**P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P314 Get medical advice/attention if you feel unwell.**P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.**P362+P364 Take off contaminated clothing and wash it before reuse.**P405 Store locked up.**P403+P235 Store in a well-ventilated place. Keep cool.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = *2

Fire = 3

Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

7440-66-6	zinc powder -zinc dust (stabilized)	60-100%%
64742-95-6	Solvent naphtha (petroleum), light arom.	5-10%%
1330-20-7	xylene	1-5%%
14807-96-6	Talc (Mg3H2(SiO3)4)	1-5%%
1314-13-2	zinc oxide	1-5%%
101-68-8	4,4'-methylenediphenyl diisocyanate	1-5%%
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	1-5%%
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	0.1-1%%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm

REL Long-term value: 0.05 mg/m³, 0.005 ppm
Ceiling limit value: 0.2* mg/m³, 0.02* ppm
*10-min

TLV Long-term value: 0.051 mg/m³, 0.005 ppm

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 4)

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

• **Breathing equipment:**

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Fluid
Color:	Various colors
Odor:	Aromatic
Odour threshold:	Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	190 °C (374 °F)

• **Flash point:** 24 °C (75 °F)

• **Flammability (solid, gaseous):** Not applicable.

• **Ignition temperature:** 450 °C (842 °F)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	2.82-2.98 g/cm ³ (23.533-24.868 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Solids content:	88-90 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

1314-13-2 zinc oxide

Oral	LD50	> 5000 mg/kg (rat)
------	------	--------------------

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral	LD50	2200 mg/kg (mouse)
------	------	--------------------

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral	LD50	> 6000 mg/kg (rat)
------	------	--------------------

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 6)

Dermal	LD50	> 3000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 7.8 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2B
101-68-8	4,4'-methylenediphenyl diisocyanate	3
9016-87-9	diphenylmethanediisocyanate, isomers and homologues	3
111-76-2	2-butoxyethanol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015





Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	<p>UN1263</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT, IATA · ADR · IMDG 	<p>Paint 1263 Paint, ENVIRONMENTALLY HAZARDOUS PAINT (zinc powder -zinc dust (stabilized), zinc oxide), MARINE POLLUTANT</p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<p></p> <p>3 Flammable liquids</p>
<ul style="list-style-type: none"> · Class · Label 	<p>3 3</p>
<ul style="list-style-type: none"> · ADR, IMDG 	<p> </p> <p>3 Flammable liquids</p>
<ul style="list-style-type: none"> · Class · Label 	<p>3 3</p>
<ul style="list-style-type: none"> · IATA 	<p></p> <p>3 Flammable liquids</p>
<ul style="list-style-type: none"> · Class · Label 	<p>3 3</p>
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: · Special marking (ADR): 	<p>Product contains environmentally hazardous substances: zinc powder -zinc dust (stabilized) Yes Symbol (fish and tree) Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids 30 F-E,S-E A</p>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	<p>Not applicable.</p>

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 8)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

1314-13-2 zinc oxide

101-68-8 4,4'-methylenediphenyl diisocyanate

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

111-76-2 2-butoxyethanol

· **TSCA (Toxic Substances Control Act):**

Solvent naphtha (petroleum), light arom.

xylene

Talc (Mg₃H₂(SiO₃)₄)

zinc oxide

4,4'-methylenediphenyl diisocyanate

diphenylmethanediisocyanate, isomeres and homologues

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7440-66-6 zinc powder -zinc dust (stabilized)

II

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 9)

1330-20-7	xylene	I
1314-13-2	zinc oxide	D, I, II
101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD
111-76-2	2-butoxyethanol	NL

· **TLV (Threshold Limit Value established by ACGIH)**

xylene	A4
Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word Danger**

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.
4,4'-methylenediphenyl diisocyanate
Talc (Mg₃H₂(SiO₃)₄)
diphenylmethanediisocyanate, isomeres and homologues

· **Hazard statements**

H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H340 May cause genetic defects.
H350 May cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P284 [In case of inadequate ventilation] wear respiratory protection.
P280 Wear protective gloves / eye protection / face protection.
P240 Ground/bond container and receiving equipment.
P233 Keep container tightly closed.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321 Specific treatment (see on this label).
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P363 Wash contaminated clothing before reuse.
P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P308+P313 IF exposed or concerned: Get medical advice/attention.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 11/02/2015

Reviewed on 10/29/2015

Trade name: MC-ZINC 2.8

(Contd. of page 10)

P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**
- **Additional classification according to Decree on Hazardous Materials:**
Carcinogenic hazardous material group III (dangerous).
- **Information about limitation of use:**
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
Exceptions can be made by the authorities in certain cases.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** HS REG.DEPART.REG.SS
- **Date of preparation / last revision** 11/02/2015 / -
- **Abbreviations and acronyms:**
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids, Hazard Category 3
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
 Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
 Carc. 1B: Carcinogenicity, Hazard Category 1B
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2